



Anti-Mould & Blackspot Matt Finish Paint

Technical Data Sheet

Product Information

DESCRIPTION

A washable, decorative fungicidal, anti-mould, matt finish paint for areas susceptible to mould and bacterial growth.

USAGE/PURPOSE

For internal use on any above ground surface to eliminate mould, algae and fungus.

CHARACTERISTICS

Environmentally friendly, water-borne formulation

PERFORMANCE

Non-toxic and odour free when dry
Non caustic and non-injurious to the skin
Mould will not grow for the life of the paint film

FINISH

Matt.

COLOUR: White or Magnolia

Please contact the Technical Services Department for colour options.

ENVIRONMENTAL CONSIDERATIONS

Water-borne. Contains no added lead

PACKAGING

Can size: 1L; 2.5L; 5L

Technical Specification

COMPOSITION

Water based resin with inorganic pigments and fungicidal additives

PROPERTIES

VOC content: 28g/l

Cat. A: 75g/l (2007)/30g/l (2010)

CONTAINS

3-IODO-2 PROPYNYL-N BUTYL-CARBONATE 0.594% W/W.

Surface Preparation

Remove grease, dirt, mould, rust and all loose flaking material back to a sound surface. Make good any defective surfaces to a smooth finish. Tape exposed copper pipes.

If there is organic growth:

Remove with a stiff bristle (not wire) brush and apply a liberal coat of Proud Paints Sterilising Solution.

For any metal surfaces:

Apply appropriate metal primer

For any bare copper surfaces:

Cover with tape, or apply a suitable metal primer.

Application

METHOD

Stir thoroughly before use
Apply 2 coats by brush, roller or spray.
Remove splashes immediately from adjacent trim to be painted in conventional gloss finish.

RECOMMENDED FILM THICKNESS

Wet: 65 microns

Dry: 30 microns

THINNING

For absorbent surfaces, first coat may be thinned with water up to 10% max.

COVERAGE

11 -13m² per liter, per coat, depending upon type of surface.

DRYING TIME

4 hours in dry, well-ventilated conditions.

CLEANING

Clean all equipment thoroughly with water immediately after use.

LIMITATIONS

Not recommended for use in extremely humid conditions or where frequent scrubbing occurs.

NOTE: If Proud Paints Anti Mould products are over-painted with anything other than Proud Paints products, the fungicidal properties will be lost.

Health & Safety Notes

SAFETY

Before use, refer to **Material Safety Data Sheet**. Lift product with care.

HEALTH

For interior use only
Wear suitable protective clothing (*coveralls*) and synthetic rubber or PVC gloves.

Do not breathe spray mist.
Do not contaminate foodstuffs, eating utensils or food contact surfaces

Cover water storage tanks before application

The (COSHH) Control of Substances Hazardous to Health Regulations 1999 may apply to the use of this product at work

This material and its container must be disposed of in a safe way. Do not contaminate watercourses or ground

Read all precautions before use (*HSE No. 7280*)

PRECAUTIONS

Wash splashes from skin or eyes immediately. Wash hands and exposed skin before meals and after use.

Keep in original container tightly closed in a safe place.



ENVIRONMENTAL

Do not empty into drains or watercourses.

Local Authorities have special facilities for the disposal of waste paint materials and cans.

Contractors: Use a paints recycling company to dispose of materials & cans. Call our office for guidance on any disposal questions.

ADDITIONAL INFORMATION

Contains no added lead

Proud Paints Limited cannot accept liability for damage caused by spillage. This product is approved under the Control of Pesticides Regulations 1986, for use as directed. HSE No.7280

STORAGE

Store in secure, dry conditions at temperature between 5° and 28°C. Protect from frost.

Containers should be kept closed during storage. Avoid spillage and contamination. Do not empty into drains and water courses.

SHELF LIFE

1 year in original, unopened container, if stored in accordance with recommendations above.

Specification

Fully written model propriety specifications for Proud Paints products are available from our Technical Services Department.

QUALITY CONTROL

All Proud Paints products are checked before release using the latest techniques to ensure controlled, consistent high quality.

Manufacturing Information

Manufactured under a quality system approved by the BSI to ISO 9001 –2008.



Additional Information

TECHNICAL ASSISTANCE

For further information, advice or guidance regarding any aspect of Proud Paints products, please contact the Technical Services Department at the address below.

WARRANTY

As Proud Paints has no direct control over the methods employed by the user in applying its products, any warranty either written or implied, is given in good faith and can only cover the material itself.